

XAS 185 KD iT4

Purpose built for the most demanding job sites and conditions, the Atlas Copco XAS 185 HardHat™ will stand the test of time.



Atlas Copco



ALL THE OPTIONS YOU NEED FOR YOUR SPECIFIC APPLICATIONS

The Hardhat features a revolutionary polyethylene canopy design - the toughest in the industry. It will not rust, dent, corrode or fade, and it resists extreme temperatures. The canopy protects the compressor from damage at the worksite, which helps reduce the cost of ownership and boost resale value. Because it can "take a beating" in a variety of applications, it's ideal for the rental industry.

Technical data

Model	XAS 185 KDIT4	
Actual Free Air Delivery*	cfm	185
Working Pressure @ Rated Flow	psi (Bar)	100
Working Pressure Range	psi (Bar)	58-125
Discharge Outlet Quantity		2 x 3/4"
Oil Capacity	Gal (L)	2.25 (8.5)

Engine - Kubota		
Model	V2403-M-DI-E3B	
Displacement	L	2.4
Cylinders		4
Tier	US EPA	Interim Tier 4
Power	HP	49
Rated Speed (high)	RPM	2700
Rated Speed (low)	RPM	1600
Fuel Tank Capacity	Gal(L)	20 (75)
Fuel Consumption @ 100% FAD	Gal/hr (L/hr)	2.3 (8.7)
Sound pressure Level dBA @ 23' (7m) @ 75% load	dB(A)	76

Dimensions (L x W x H) & Weight		
Trailer	in / mm	127 x 64 x 61 / 3226 x 1626 x 1549
Weight (wet), Trailer Mounted	lbs / kg	2330 / 1059

*According to ISO1217 ed.3 1998 annex D

Photos and illustrations contained herein might depict products with optional and/or extra components which are not included with the standard version of the product and, therefore, are not included in a purchase of such product unless the customer specifically purchases such optional/extra components. We reserve the right to change the specifications and design of products described in this literature without notice. Not all products are available in all markets.

STANDARD FEATURES

- Extremely reliable 49 HP Kubota engine (EPA compliant)
- The most efficient air end in the compressor industry
- Control panel conveniently located at waist level
- Discharge valves on the same end as control panel
- Easy access to filters and the oil separator tank
- Road lights standard
- Extremely durable body
- Removable baffle for easy cleaning
- Award-winning design
- Thermostatic by-pass valve, for superior cold climate operation
- 15" wheels
- Block heater
- Heavy duty battery
- Synthetic oil

OPTIONS

- 50' single hose reel
- 50' dual hose reel
- 100' single hose reel
- 100' dual hose reel
- 2" adjustable bulldog hitch
- 18" extended drawbar with jockeywheel
- Toolbox, external



*Optional fuel gauge shown



Tier4